DIGITAL FILTER FOR SUB-BAND SYNTHESIS

BACKGROUND OF THE INVENTION

1. Field of the Invention

5   The present invention relates to digital filters and more
particularly to a sub-band decoder having a reduced memory
size and a method of performing an inverse discrete cosine
transform that generates time domain samples from frequency
domain samples using a limited number of prestored cosine
10   coefficients.

2. Description of Related Art

Audio and video files, before being compressed, typically
consist of 16 bit samples recorded at a sampling rate more
than twice the actual audio bandwidth (e.g., 44.1 kHz for
15   Compact Disks), which yields more than 1.4 Mbit to represent
just one second of stereo music in CD quality. Since such
vast amounts of data are unwieldy, data compression is
required.

MPEG (Motion Picture Experts Group) provides standards
20   for compressing digital audio and video signals. MP3 (MPEG
Layer 3) is the MPEG layer 3 audio standard. Using MPEG audio
coding, the original sound data can be reduced by a factor of
12, without sacrificing sound quality. Audio data in an MPEG
compatible data stream is commonly referred to as the audio
25   sub-band. According to MPEG standards, the audio sub-band
contains sets of 32 code values that are frequency domain
samples S_k. Decoding 32 frequency domain samples S_k, where k
is a frequency index and ranges from 0 to 31, generates 64
time domain sound samples V_i, where i is a time index and
30   ranges from 0 to 63. Recently MP3 audio files have become
very popular and as a result, MP3 has become the de facto
standard for storing audio files, with many MP3 files

1

available on the Internet and many programs that support the MP3 standard.

Fig. 1 is a schematic block diagram of a conventional MP3 decoder 10. The decoder 10 receives an encoded MP3 bit stream
5   and converts it to an analog audio output signal that is a single PCM coded signal that sounds identical to the original audio signal. More specifically, the MP3 bit stream is a sequence of many frames, each containing a header, error checking bits, miscellaneous information, and encoded data.

10   At block 12, the MP3 bit stream is received and upon detection of a sync-word indicating the start of a frame, the decoder 10 identifies the header and side information. Next, at block 14, the decoder 10 obtains scale factors. Then, the decoder 10 must decode the samples, which are coded using
15   Huffman codes, at block 16. Huffman coding can pack audio data very efficiently. Further, Huffman coding is lossless because no noise is added to the audio signal.

After a bit pattern is decoded, it is dequantized at block 18 using a non-linear dequantization equation, and at
20   block 20, reorder, anti-alias and stereo processing are performed on the samples. Next, at block 22, an Inverse Modified Discrete Cosine Transform (IMDCT) is performed on the frequency domain samples. Finally, at block 24, sub-band synthesis is performed to transform the frequency domain sub-
25   band sample back to a time domain PCM audio signal. The sub-band synthesis is the most computation intensive part of the signal processing, typically taking more than half of the total decoding time.

Sub-band synthesis has two main parts, an IDCT (Inverse
30   Discrete Cosine Transform) process that generates time domain samples from frequency domain samples and a windowing process that generates the final PCM output signal. More

2

particularly, the IDCT process generates 64 samples (V_i) from 32 input sub-band samples (S_k). Using direct matrix processing, for i = 0 to 63,

$$V_i = \sum_{k=0}^{31} \cos\ ((\pi/64)(i+16)(2k+1))\ \times\ S_k \qquad (1)$$

requires about 2,000 additions and about 2,000 multiplications to be performed.

In addition, when the decoder 10 is implemented with a DSP, MCU, microprocessor or dedicated hardware that processes data in real-time, the cosine coefficients must be obtained quickly. One conventional method of obtaining the cosine coefficients is to calculate them directly using an estimation method or by calling a library cosine function. Each calculation/estimation of **cos** requires greater than 60 cycles.

Referring to Fig. 2, a second conventional method is to store the coefficients in a 32x64 array. Fig. 2 shows a 32x64 matrix of cosine coefficients, where C = cos $((\pi/64)(i+16)(2k+1))$. Assuming each coefficient is stored in a 32 bit memory space, then 8k bytes of memory are required (32 x 64 x 4 bytes/word = 8192 bytes).

Yet another known method of obtaining the cosine coefficients is to extract and store only certain, symmetric ones of the coefficients, as disclosed in U.S. Patent No. 6,094,673. According to this patent, the 32x64 matrix is reduced to 16x32, which requires that only 496 coefficients be stored. However, storing 496 coefficients still requires 1984 bytes of memory (496 x 4 bytes/word = 1984).

While large tables are readily formed without concern for the amount of memory used by decoders such as in MP3 players implemented on personal computers, with the increase in the popularity of MP3 files for storing music, there has been a

corresponding increase in the demand for miniature stand-alone MP3 devices and other, small portable devices such as mobile telephones and personal digital assistants (PDAs) capable of playing MP3 encoded music. It would be beneficial if this

5   memory requirement could be further reduced for such portable devices without requiring a large corresponding increase in computational requirements.

SUMMARY OF THE INVENTION

10   The present invention provides a digital filter for sub-band synthesis that prestores only predetermined ones of the cosine coefficients required to perform an inverse discrete cosine transform process that generates time domain samples from frequency domain samples. The present invention further

15   provides a method of performing an IDCT process that generates time domain samples from frequency domain samples using prestored cosine coefficients and cosine coefficients calculated using the prestored coefficients.

Accordingly, a first embodiment of the invention

20   provides, in a digital filter for sub-band synthesis, a method of performing an IDCT process that generates time domain samples from frequency domain samples using prestored cosine coefficients, including the steps of prestoring only the cosine coefficients that satisfy $\cos (\pi * (i/64))$ for $i = 0$ to

25   32, and calculating cosine coefficients for $i = 33$ to 63 using the prestored coefficients by changing a sign of a corresponding symmetrical one of the stored coefficients, respectively.

A second embodiment of the invention provides, in a

30   digital filter for sub-band synthesis, a method of performing an IDCT process that generates time domain samples from

4

frequency domain samples using prestored cosine coefficients, including the step of prestoring only the cosine coefficients that satisfy cos $(\pi * (i/64))$ for $i = 0$ to 63.

The invention further provides, in a digital filter for sub-band synthesis, a method of performing an IDCT process that generates time domain samples from frequency domain samples using prestored cosine coefficients, including the steps of prestoring only the cosine coefficients that satisfy cos $(\pi * (i/64))$ where $i = 0-32$, calculating the cosine coefficients for $i = 33-63$ using the stored coefficients by changing a sign of a corresponding symmetrical one of the stored coefficients, respectively, and generating sixty-four samples (V_i) from thirty-two sub-band samples (S_k) according to the equation,

$$V_i = \sum_{k=0}^{31} \cos ((\pi/64)(i+16)(2k+1)) \ x \ S_k$$

for $i = 0$ to 63, using the prestored cosine coefficients and the calculated cosine coefficients.

In a third embodiment, the invention provides a method of performing an IDCT process that generates time domain samples (V_i) from frequency domain samples (S_k) using prestored cosine coefficients, where i and k are integer values defining columns and rows respectively of a matrix of cosine coefficients. The method includes the steps of prestoring the cosine coefficients $C(k-1,i)$ and $C(k-2,i)$ for each column of the matrix, prestoring an adjustment value cos$(E(i))$ for each column of the matrix, and calculating the cosine coefficients for the remaining locations in the matrix using the prestored coefficients and the prestored adjustment values in accordance with the equation $C(k,i) = 2 \cos(E(i)) * C(k-1,i) - C(k-2,i)$.

Yet another embodiment of the invention provides a method of performing an IDCT process that generates time domain samples (V_i) from frequency domain samples (S_k) using prestored cosine coefficients, where i and k are integer values defining columns and rows respectively of a matrix of cosine coefficients, including the steps of prestoring the cosine coefficients $C(k,i)$ and $C(k-1,i)$ for each column of the matrix, prestoring an adjustment value $\cos(E(i))$ for column of the matrix, and calculating the cosine coefficients for the remaining rows and columns of the matrix using the prestored coefficients and the prestored adjustment values in accordance with the equation, $C(k+1,i) = 2\cos(E(i)) * C(k,i) - C(k-1,i)$.

The present invention further provides a digital filter for sub-band synthesis that includes a memory for prestoring only the cosine coefficients that satisfy $\cos(\pi * i/64)$ for $i = 0$ to 32, and a processor, connected to the memory for receiving the prestored cosine coefficients, for performing an IDCT process that generates time domain samples from frequency domain samples using the prestored cosine coefficients, wherein the processor calculates cosine coefficients for $i = 33$ to 63 using the prestored coefficients by changing a sign of a corresponding symmetrical one of the prestored coefficients, respectively.

The invention also provides a digital filter for sub-band synthesis, comprising a memory for prestoring only the cosine coefficients that satisfy $\cos(\pi * (i/64))$ for $i = 0$ to 63 and a processor, connected to the memory and receiving the prestored cosine coefficients, for performing an IDCT process that generates time domain samples from frequency domain samples using the prestored cosine coefficients, wherein the processor generates sixty-four time domain samples (V_i) from

6

thirty-two frequency domain samples (S_k) according to the
equation

$$V_i = \sum_{k=0}^{31} \cos\left((\pi/64)(i+16)(2k+1)\right) \times S_k$$

for $i = 0$ to 63, using only the prestored cosine coefficients.

The present invention also provides a digital filter for
sub-band synthesis via an IDCT process that generates time
domain samples (V_i) from frequency domain samples (S_k), where i
and k are integer values defining columns and rows
respectively of a matrix of cosine coefficients, the digital
filter comprising a memory for prestoring the cosine
coefficients $C(k-1,i)$ and $C(k-2,i)$ for each column of the
matrix and an adjustment value $\cos(E(i))$ for each column of
the matrix, and a processor for calculating the cosine
coefficients for the remaining locations in the matrix using
the prestored coefficients and the prestored adjustment values
in accordance with the equation $C(k,i) = 2\cos(E(i)) * C(k-1,i)$
$- C(k-2,i)$.

Finally, the present invention provides a digital filter
for sub-band synthesis via an IDCT process that generates time
domain samples (V_i) from frequency domain samples (S_k), where i
and k are integer values defining columns and rows
respectively of a matrix of cosine coefficients, the digital
filter comprising a memory for prestoring the cosine
coefficients $C(k,i)$ and $C(k-1,i)$ for each column of the matrix
and an adjustment value $\cos(E(i))$ for each column of the
matrix, and a processor for calculating the cosine
coefficients for the remaining rows and columns of the matrix
using the prestored coefficients and the prestored adjustment
values in accordance with the equation, $C(k+1,i) = 2\cos$
$(E(i)) * C(k,i) - C(k-1,i)$.

7

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing summary, as well as the following detailed description of preferred embodiments of the invention, will be better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, there is shown in the drawings embodiments that are presently preferred. It should be understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown. In the drawings:

Fig. 1 is a schematic block diagram of a conventional MP3 decoder;

Fig. 2 illustrates a 32x64 matrix of cosine coefficients used by the MP3 decoder of Fig. 1;

Fig. 3 is a graph showing cosine values stored in a memory according to a first embodiment of the present invention;

Fig. 4 is a graph showing cosine values stored in a memory according to a second embodiment of the present invention;

Fig. 5 is a graph illustrating a relationship of cosine values used in a sub-band decoder in accordance with a third embodiment of the present invention;

Fig. 6 is a diagram illustrating a reduction in the size of the matrix of cosine coefficients stored in a memory of a sub-band decoder in accordance with the present invention; and

Fig. 7 is a high level block diagram of a digital filter in accordance with the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

In the drawings, like numerals are used to indicate like elements throughout.

8

The present invention provides a digital filter for sub-band synthesis that processes input data and calculates the cosine coefficients in parallel and does not require a large amount of memory for storing cosine coefficients. The present invention further provides a method for performing an IDCT process that generates time domain samples from frequency domain samples using prestored cosine coefficients.

As discussed above, known methods of performing the IDCT process require a relatively large amount of memory to store the cosine coefficients. According to the present invention, the number of cosine coefficients stored is reduced and the others are calculated. However, because of the cosine coefficients selected to be stored, such calculation is performed very quickly.

Analyzing the equation used to perform IDCT, for $i = 0$ to 63,

$$V_i = \sum_{k=0}^{31} \cos \left((\pi/64)(i+16)(2k+1) \right) \times S_k$$

it can be seen that there are many duplicates in the 32x64 matrix. First observe that i and k are positive integers, so $(i+16)(2k+1)$ must be some integer. Hence we only need to store $\cos(\pi * i/64)$, or 64 cosine coefficients. Fig. 3 is a graph illustrating the 64 cosine values prestored in a memory according to a first embodiment of the invention. The other 1984 coefficients of the 32x64 matrix have values that are the same as the 64 stored values. Thus, according to the first embodiment of the invention, the cosine coefficients that satisfy the equation $\cos(\pi * i/64)$ for $i = 0$ to 63, are prestored in a memory. Then, the time domain samples (V_i) are calculated from the frequency domain samples (S_k) according to the equation (1) above using the prestored cosine coefficients.

9

The first embodiment stores 64 cosine coefficients.
However, this number can be reduced further. Referring to
Fig. 4, a graph showing cosine values stored in a memory
according to a second embodiment of the invention is shown.
5   The graph of Fig. 4 shows that the number of coefficients
stored can be halved because the cosine values in the range
$(0\pi/64 \ldots 31\pi/64)$ are an exact mirror of the cosines values
in the range $(64\pi/64 \ldots 33\pi/64)$, with the opposite sign. For
example, $33\pi/64 = -(31\pi/64)$. Thus, according to the second
10 embodiment of the invention, only 33 cosine coefficients are
prestored in memory. That is, according to the second
embodiment, only the cosine coefficients that satisfy cos (π *
$i/64$) for $i = 0$ to 32 are prestored in memory and the cosine
coefficients for $i = 33$ to 63 are calculated using the
15 prestored coefficients simply by changing a sign of a
corresponding symmetrical one of the stored coefficients.
Then, the time domain samples (V_i) are calculated from the
frequency domain samples (S_k) according to the equation (1)
above, using only the prestored cosine coefficients and the
20 calculated cosine coefficients.
The index for obtaining the correct cosine coefficient to
plug into the equation may be generated, for example, with the
pseudo-code shown in table 1.

```
25   Index = (i+16)(2k+1);
     Index = Index & 0x007f;              // Keep index in range 0..127
     If (Index>63) then Index = 128-Index;  // Fold 3rd & 4th quadrant;
      (Index = 0..32) then {
       Answer = Cosine_Table[Index];
30   }else{
       Index = 64 - Index;               // Fold 2nd quadrant;
       Answer = Negative (Cosine_Table[Index]);
     }
                              TABLE 1
35
```

Although this method is memory efficient, it consumes some
processor time for index calculation and other overhead such
as conditional branches and instruction pipelines. As is
understood by those of skill in the art, branch or jump
5   instructions generally require more cycles to process than an
add or multiply instruction. Using a convention digital
signal processor (DSP), about 8-10 cycles are used per access
to calculate the index. The index calculation is simpler if
all 64 coefficients are stored, as per the first embodiment.
10   It is a trade-off between memory space and processing/memory
access time.

        Referring again to Fig. 2 to observe the cosine matrix,
the matrix may be viewed as a set of 64 cosine series and then
make use of the relation between adjacent cosine values. When
15   i and k are put into the equation (1), we observe that the
cosine coefficients are related. For example, for the first
column of the matrix, when $i = 0$ and $k = 0..31$, the following
cosine values are generated:

        $\cos(\pi/64*16*1)$
20      $\cos(\pi/64*16*3)$
        $\cos(\pi/64*16*5)$
        $\cos(\pi/64*16*7)$
        $\cos(\pi/64*16*9)$
                :
25   :
        $\cos(\pi/64*16*61)$
        $\cos(\pi/64*16*63)$

        Referring now to Fig. 5, a graph of the relationship of
30   the cosine values generated is shown. Note that the angle of
the cosine value increased by a constant amount **E**. In this
case, **E** $= (\pi/64*16*2)$. The same relationship is true for
other cosine series (columns) in the matrix, though the angle
and the angle difference **E** may be some other value.

11

Since we know that the coefficients differ by a constant angle, we can derive the next coefficient using the previous coefficients. Using the equalities for sine and cosine:

5   COS(X+Y) = COS(X)*COS(Y)-SIN(X)*SIN(Y),
       SIN(-Z) = -SIN(Z), and
       COS(-Z) = COS(Z)

Along a column where i is unchanged and k varies, suppose the
10   **n**-th coefficient, C(n) equals COS(**a**), for some angle **a**. The
next coefficient, C(n+1) equals COS(**a+E**), where **E** is the angle
difference. The previous coefficient, C(n-1) equals COS(**a-E**).
Using the equalities above, the equation may be rewritten as
follows.

15
      C(n+1)+C(n-1) = COS(a+E) + COS(a-E)
                    = COS(a)COS(E) - SIN(a)SIN(E) + COS(a)COS(-E) - SIN(a)SIN(-E)
                    = COS(a)COS(E) - SIN(a)SIN(E) + COS(a)COS(E) + SIN(a)SIN(E)
                    = 2COS(a)COS(E)
20   = C(n) * 2COS(E)

Hence, the next coefficient, C(n+1) = 2cos(**E**)*C(n) - C(n-1).
Cos(**E**) is a constant, as long as i is unchanged. So, it is
clear that for each i (each column), instead of storing 32
coefficients, we only need to store 3 coefficients, the last 2
25   samples: C(n-1) and C(n-2) and the adjustment value 2*cos(**E**).
As there are 64 columns in the matrix, each column can be
represented by 2 coefficients and an adjustment value, so the
total number of storage locations required is 3*64 or 192
locations.
30   Although the third embodiment requires more memory space
than the first and second embodiments above, which stored 64
and 33 coefficients, respectively, the third embodiment
requires much less processor time to perform coefficient
35   calculation than the first and second embodiments because the

12

memory does not need to be accessed as often and calculation
of the index (memory address) is simpler and also because
fewer jumps (conditional and unconditional) must be executed.
The number of coefficients stored in the third embodiment is
5   90.5% less than for the conventional 32x64 matrix.

Fig. 6 is a diagram illustrating a reduction in the size
of the matrix of cosine coefficients stored in a memory of a
sub-band decoder in accordance with the present invention.
Fig. 6 shows a conventional 32x64 matrix 60 of cosine
10 coefficients and a reduced size 3x64 matrix 62 that includes
two cosine coefficients (C(n-1), C(n-2)) for each column and
an adjustment value cos(E) for each column.

Thus, the third embodiment of the present invention
provides a method of performing an IDCT process that generates
15 time domain samples (V_i) from frequency domain samples (S_k)
using prestored cosine coefficients, where i and k are integer
values defining columns and rows respectively of a matrix of
cosine coefficients. The method comprises prestoring the
cosine coefficients $C(k-1,i)$ and $C(k-2,i)$ for each column i of
20 the matrix and prestoring an adjustment value $cos(E(i))$ for
each column of the matrix. Then, the cosine coefficients for
the remaining locations in the matrix are calculated using the
prestored coefficients and the prestored adjustment values
according to the equation $C(k,i) = 2 \cos(E(i)) * C(k-1,i) -$
25 $C(k-2,i)$. The prestored adjustment values $cos(E(i))$ are
calculated as $\cos(\pi/64 * (i+16) * 2)$.

Alternatively, instead of being used for sub-band
synthesis, the third embodiment can be applied to other
situations in which the cosine/sine coefficients in a matrix
30 are related. That is, where the angle increases by a constant
value. For example, the method may be used in the IMDCT

13

process performed in layer 3 decoding. In such a case, the
adjustment value $\cos(E(i))$ is calculated as $\cos(\pi/72 * (2i+19) * 2)$ or as $\cos(\pi/24 * (2i+7) * 2)$, depending on the size of
the matrix used, for example, 18x36 and 6x12, as will be
5   understood by those of skill in the art.

In the IDCT process, the prestored and calculated cosine
coefficients are used to generate the time domain samples (V_i)
from the frequency domain samples (S_k) by solving the equation
(1) above.

10   The third embodiment of the present invention may be
modified in order to reduce the size of the stored coefficient
matrix 62 (Fig. 6) even further. Analyzing the values stored
in the matrix, we can see that the adjustment values
$\cos(E(i))$, as well as the coefficient values $C(n-1)$ and $C(n-2)$
15   increase by a constant amount from column to column. For
example, observing the values stored in the 3x64 matrix 62,
when $i = 0$ to 63, the following values are stored:

	$i=0$	$i=1$	$i=2$ ... $i=63$
$\cos(E)$	$\cos(\pi/64*16*2)$,	$\cos(\pi/64*17*2)$,	$\cos(\pi/64*18*2)$ ...
$C(n-1)$	$\cos(\pi/64*16*(2*(-1)+1))$	$\cos(\pi/64*17*(2*(-1)+1))$	$\cos(\pi/64*18*(2*(-1)+1))$ ...
$C(n-2)$	$\cos(\pi/64*16*(2*(-2)+1))$	$\cos(\pi/64*17*(2*(-2)+1))$	$\cos(\pi/64*18*(2*(-2)+1))$ ...

25   Thus, as i increases, the cosine angle increases by a constant
amount of $E'=(\pi/64*1*2)$. Similarly, the prestored rows of
cosine coefficients increase by a constant amount. The $C(n-1)$
row increases by $\cos(\pi/64*1*(2*(-1)+1))$ and the $C(n-2)$ row
increases by $\cos(\pi/64*1*(2*(-2)+1))$. The same method used to
30   reduce the number of stored rows of coefficients can be used
to reduce the number of stored columns of coefficients, by
making use of the relationship between cosine coefficients
horizontally. That is, for the columns of coefficients, only
the columns for $C(k,i-1)$ and $C(k,i-2)$, and corresponding

14

column adjustment values cos(E') need to be stored. In this manner, the size of the matrix is reduced from 3x64 to just 3x3 or 9 values.

Referring again to Fig. 6, the matrix reduction is shown beginning with the conventional 32x64 matrix 60 of cosine coefficients to the reduced size 3x64 matrix 62 that includes two cosine coefficients (C(n-1), C(n-2)) for each column and an adjustment value cos(E) for each column, to a 3x3 matrix 64 having just 4 coefficient values and 5 adjustment values.

A sub-band synthesis filter according to the modified third embodiment of the present invention, which requires storing only a 3x3 matrix, has been implemented and tested on a Motorola SC140 DSP core. The Motorola SC140 DSP core is a high performance DSP Core having four ALUs (Arithmetic & Logic Unit) and 2 AGUs (Address Generation Unit) that is commercially available from Motorola Inc. of Schaumburg Illinois.

Fig. 7 shows a high level block diagram of a digital sub-band filter 70 according to the present invention. The filter 70 includes a memory 72 in which a predetermined number of cosine coefficients are stored and a processor 74, such as the above-mentioned Motorola SC140 DSP connected to the memory for processing the MP3 bit stream input, including accessing the prestored coefficients, calculating the other coefficients and generating the PCM signal.

During implementation, it was determined that the algorithm is processed faster if, instead of storing the coefficients C(n-1) and C(n-2) for each column, the coefficients C(n) and C(n-1) are stored, so that an initial calculation of C(n) does not need to be performed. Then, as the other cosine values are calculated for that column, instead of calculating the current cosine value, the next

15

cosine value is calculated. This allows for parallel calculations to be performed. More particularly, a first group of the cosine coefficients and a second group of the cosine coefficients are calculated in parallel using separate
5   processors. The first group of cosine coefficients is $\cos(k+2, i)$ for k=0, 2, 4, … 14 and the second group of cosine coefficients is $\cos(k+2, i)$ for k=1, 3, 5, … 15.

In addition, the storage of coefficients can be further reduced by one-third because the value of the coefficients
10   when k=0 is the same as when k=(-1).

As is apparent from the above, the present invention provides data structures for sub-band synthesis that require less memory space, yet still allow for efficient calculation of cosine coefficients. While the foregoing discussion
15   describes the invention in terms of an MP3 decoder, it will be understood by those of ordinary skill in the art that the invention is applicable to other types of decoders. For example, the invention is applicable to other applications that require sub-band decoding, such as JPEG (Joint
20   Photographic Experts Group) imaging systems like desktop video editing, digital still cameras, surveillance systems, video conferencing and other consumer products.

It will be appreciated by those skilled in the art that changes could be made to the embodiments described above
25   without departing from the broad inventive concept thereof. It is understood, therefore, that this invention is not limited to the particular embodiments disclosed, but it is intended to cover modifications within the spirit and scope of the present invention as defined by the appended claims.